

KAWASAKI WHEELED LOADERS 65 ZIII

ISUZU 6BG1



ENGINE Isuzu 6BG1

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 250 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 30*Change every 250 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40*Change every 250 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours*

DIFFERENTIAL FRONT

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 2000 hours*

DIFFERENTIAL REAR

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 2000 hours*

KAWASAKI WHEELED LOADERS 65 ZIII

ISUZU 6BG1



HUB REDUCTIONS FRONT

| USE | | CLIMATE |
|--------------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Change every 2000 hours</i> | | |

HUB REDUCTIONS REAR

| USE | | CLIMATE |
|--------------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Change every 2000 hours</i> | | |

TRANSMISSION Powershift

| USE | | CLIMATE |
|--------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 10W | ATF Dexron II-D | |
| <i>Change every 1000 hours</i> | | |

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus AF 100 | | |
| <i>Change every 2000 hours</i> | | |

| USE | | CLIMATE |
|--------------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |
| <i>Change every 2000 hours</i> | | |

| USE | | CLIMATE |
|--------------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |
| <i>Change every 2000 hours</i> | | |

KAWASAKI WHEELED LOADERS 65 ZIII

ISUZU 6BG1



HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

| | | |
|---------------|--|---------------------|
| USE Normal | | CLIMATE Moderate |
|---------------|--|---------------------|

| | | |
|--|---|--|
| PRODUCT RECOMMENDATION 1 Labora Grease | PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2 | PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2 |
|--|---|--|

| | | |
|---------------|--|-------------------|
| USE Normal | | CLIMATE Arctic |
|---------------|--|-------------------|

| | | |
|---|--|--|
| PRODUCT RECOMMENDATION 1 Gear Grease EP 1 | | |
|---|--|--|

STEERING GEARBOX

| | | |
|---------------|--|--------------------------|
| USE Normal | | CLIMATE Mediterranean |
|---------------|--|--------------------------|

| | | |
|---|--|--|
| PRODUCT RECOMMENDATION 1 Gearlube HS GL-5 80W-140 | | |
|---|--|--|

| | | |
|---------------|--|---------------------|
| USE Normal | | CLIMATE Moderate |
|---------------|--|---------------------|

| | | |
|---|--|--|
| PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90 | PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90 | |
|---|--|--|

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.