KAWASAKI WHEELED LOADERS 95 ZV-2 CUMMINS QSX15



ENGINE Cummins QSX15 Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

DIFFERENTIAL HUB REDUCTIONS FRO Capacity: 100 liter (each hub)	NT	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Change every 2000 hours

DIFFERENTIAL HUB REDUCTIONS REA Capacity: 200 liter (each hub)	R	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
O / O O O O O O O O O O		

Change every 2000 hours

DIFFERENTIAL LIMITED SLIP		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

TRANSMISSION Capacity: 65 liter (+ torque converter)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 1000 hours	

KAWASAKI WHEELED LOADERS 95 ZV-2 CUMMINS QSX15



HYDRAULIC SYSTEM Capacity: 150 liter (Hydraulic tank), Capacity: 265 liter (Total)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		

HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 100 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 2000 hours			

KAWASAKI WHEELED LOADERS 95 ZV-2 CUMMINS QSX15



SP Gear 5015	SP Gear 1071	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Arctic
USE		CLIMATE
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Mediterranean
USE		CLIMATE
STEERING GEARBOX		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.