

# KOBELCO TRACKED EXCAVATORS SK220-IV (1995-2000)

**ENGINE**

Capacity: 17 liter

## USE

Normal

## CLIMATE

Tropical

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50**

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40****HYDRAULIC SYSTEM**

Capacity: 185 liter (Hydraulic tank), Capacity: 310 liter (Total)

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Perlus H 46**

## PRODUCT RECOMMENDATION 2

**Perlus H 68**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 32**

## USE

Normal

## CLIMATE

Cold

## PRODUCT RECOMMENDATION 1

**Perlus H 22****GREASE POINTS/NIPPLES FRONT JOINT PINS**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

# KOBELCO TRACKED EXCAVATORS SK220-IV (1995-2000)



## GREASE POINTS/NIPPLES OPERATING LEVER JOINT

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## GREASE POINTS/NIPPLES SWING INTERNAL GEAR

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## GREASE POINTS/NIPPLES TRACK ADJUSTER

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 26 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

## IDLERS

Capacity: 0,2 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Multifleet SCD 30</b> |  |          |

# KOBELCO TRACKED EXCAVATORS SK220-IV (1995-2000)



## LOWER ROLLERS

Capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

## SWING GEAR SUMP (BATH)

Capacity: 11,3 kg

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## SWING REDUCTION UNIT

Capacity: 16 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

## TRAVEL REDUCTION UNIT

Capacity: 7,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

## UPPER ROLLERS

Capacity: 0,02 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.