

KOMATSU BULLDOZERS D D155-5

**ENGINE**

Capacity: 45 liter (Dry fill), Capacity: 37 liter (Service fill)

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Change every 500 hours

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Change every 12 months

USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 250 hours/ 6 months

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

*Change every 250 hours/ 6 months***FINAL DRIVES**

Capacity: 31 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

KOMATSU BULLDOZERS D D155-5**TRANSMISSION**

Capacity: 90 liter (Refill), Capacity: 130 liter (Total)

USE		CLIMATE
Normal (alternative)		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

USE		CLIMATE
Normal (alternative)		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal (preferred)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

HYDRAULIC SYSTEM

Capacity: 85 liter (Refill), Capacity: 240 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KOMATSU BULLDOZERS D D155-5**COOLING SYSTEM**

Capacity: 82 liter

USE

Normal (preferred)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12***Change every 24 months/ 4000 hours***DAMPER CASE**

Capacity: 1,5 liter

USE

Normal (alternative)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30****USE**

Normal (preferred)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.