KOMATSU BULLDOZERS D D37PX-21 KOMATSU SAA4D102E-2 (5091->) (2003-



2008)

Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40 Change every 250 hours/ 6 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Cold PRODUCT RECOMMENDATION 1	ENGINE Komatsu SAA4D102E-2 Capacity: 12,5 liter		
PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 2 CLIMATE Dieselfleet CD+ 15W-40 CLIMATE Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	USE		CLIMATE
Multifleet SCD 30 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Change every 250 hours/ 6 months USE CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40 Change every 250 hours/ 6 months USE Normal Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	Normal		Mediterranean
Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Change every 250 hours/ 6 months USE Normal USE Normal Cold PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40 Climate Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	PRODUCT RECOMMENDATION 1		
Normal Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Synfleet SHPD 10W-40 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 2 CLIMATE CLIMATE CLIMATE CLIMATE CLIMATE COID COID COID COID COID COID COID Multifleet SCD 10W	Multifleet SCD 30		
Normal PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40 CLIMATE Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W Moderate PRODUCT RECOMMENDATION 2 CLIMATE Cold	Change every 250 hours/ 6 months		
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30 Synfleet SHPD 10W-40 Dieselfleet CD+ 15W-40 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 10W PRODUCT RECOMMENDATION 1	USE		CLIMATE
Kroontrak MTH 10W-30 Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 10W Synfleet SHPD 10W-40 Dieselfleet CD+ 15W-40 CLIMATE Cold	Normal		Moderate
Change every 250 hours/ 6 months USE Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 10W CLIMATE Cold Cold	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
USE CLIMATE Normal Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W CLIMATE Cold	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Normal Cold PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	Change every 250 hours/ 6 months		
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W	USE		CLIMATE
Multifleet SCD 10W	Normal		Cold
	PRODUCT RECOMMENDATION 1		
Change every 250 hours/ 6 months	Multifleet SCD 10W		
	Change every 250 hours/ 6 months	·	·

FINAL DRIVES		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
USE	CLIMATE	
Normal	Cold	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 1000 hours		

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 2000 hours	9,515	2.555551 1011 10	

PRODUCT RECOMMENDATION

KOMATSU BULLDOZERS D D37PX-21 KOMATSU SAA4D102E-2 (5091->) (2003-



2008)

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

TRACK IDLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 1000 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.