

PRODUCT RECOMMENDATION

KOMATSU BULLDOZERS D D65A-8 KOMATSU 6D125-1 (45001->)



ENGINE Komatsu 6D125-1
Capacity: 30 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
--	--	--

Change every 250 hours/ 6 months

FINAL DRIVES
Capacity: 31 liter

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
---	--	--

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W		
--	--	--

TORQUE CONVERTER

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		
---	--	--

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W		
--	--	--

KOMATSU BULLDOZERS D D65A-8 KOMATSU 6D125-1 (45001->)



TRANSMISSION 3/3

Capacity: 52 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

HYDRAULIC SYSTEM

Capacity: 108 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 63 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

KOMATSU BULLDOZERS D D65A-8 KOMATSU 6D125-1 (45001->)



STEERING CLUTCH CASE

Capacity: 70 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.