

KOMATSU BULLDOZERS D D85A-18

CUMMINS NT855 (26001->)



ENGINE Cummins NT855
Capacity: 43 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Change every 250 hours/ 6 months

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 250 hours/ 6 months

FINAL DRIVES

Capacity: 36 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

HYDRAULIC SYSTEM ANGLEDZOER

Capacity: 110 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 2000 hours

HYDRAULIC SYSTEM TILTDOZER

Capacity: 110 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Change every 2000 hours

KOMATSU BULLDOZERS D D85A-18

CUMMINS NT855 (26001->)



COOLING SYSTEM

Capacity: 79 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

STEERING CLUTCH CASE

Capacity: 122 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.