

KOMATSU BULLDOZERS D D85EX-18 EO

KOMATSU SAA6D125E-5 STAGE IIIA/TIER 3



ENGINE Komatsu SAA6D125E-5
Capacity: 47 liter (Dry fill), Capacity: 38 liter (Service fill)

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet MSP 10W-30	Dieselfleet MSP 15W-40

Change every 500 hours

FINAL DRIVES
Capacity: 26 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Change every 1000 hours

TRANSMISSION Komatsu Torqflow 3/3
Capacity: 90 liter (Dry fill), Capacity: 60 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 150 liter (Dry fill), Capacity: 69 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gear Oil Alcat 10W	Perlus H 46

Change every 2000 hours

KOMATSU BULLDOZERS D D85EX-18 EO

KOMATSU SAA6D125E-5 STAGE IIIA/TIER 3



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 69 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

DAMPER CASE

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 2000 hours

IDLERS

Capacity: 0,35 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.