KOMATSU TRACKED DUMP TRUCKS CD CD60R-1 S/N 2012 ->



ENGINE Komatsu S6D102 Capacity: 21,3 liter (Dry fill), Capacity: 19 liter (Refill)			
USE		CLIMATE	
Preferred		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
Change every 250 hours/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Dieselfleet MSP 15W-40			
Change every 250 hours/ 6 months			

HYDRAULIC SYSTEM Capacity: 65 liter, Capacity: 45 liter (Refill)			
USE CLIMATE			
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Dieselfleet MSP 15W-40	Gear Oil Alcat 10W	Perlus H 46	

Change every 2000 hours

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Preferred	Moderate	
PRODUCT RECOMMENDATION 1		
Q11 Xtreme Duty Grease EP 2		

Change every 100 hours

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Change every 100 hours

KOMATSU TRACKED DUMP TRUCKS CD CD60R-1 S/N 2012 ->



COOLING SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

DAMPER CASE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
<u>0</u> , , 0000, ,	

Check every 2000 hours

SWING REDUCTION UNIT Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Charle avery 1000 hours	· · ·		

Check every 1000 hours

TRAVEL REDUCTION UNIT Capacity: 2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change every 500) hours	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.