KOMATSU RIGID DUMP TRUCKS HD HD405-6 (1998-2005)



| ENGINE Komatsu SAA6D140 Capacity: 52 liter | | |
|---------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
| | | |

Change every 250 hours/ 6 months

| DIFFERENTIAL Capacity: 45 liter (Refill), Capacity: 50 liter (Specified) | | |
|--------------------------------------------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

| USE | CLIMATE |
|--------------------------|----------|
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 30 | |

| USE | CLIMATE |
|--------------------------|---------------|
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 30 | |
| USE | CLIMATE |
| Normal | Cold |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |

KOMATSU RIGID DUMP TRUCKS HD HD405-6 (1998-2005)



| HYDRAULIC SYSTEM Capacity: 129 liter (Refill), Capacity: 165 liter (Specified) | | | |
|--------------------------------------------------------------------------------|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Multifleet SCD 10W | | | |
| Change every 2000 hours | | | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 136 liter | | | |
|---------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |

| BRAKE SYSTEM FRONT Capacity: 2 liter (Tank) | |
|------------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |

| SUSPENSION FRONT Capacity: 13,8 liter | |
|------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |
| | |

PRODUCT RECOMMENDATION

KOMATSU RIGID DUMP TRUCKS HD HD405-6 (1998-2005)



| SUSPENSION REAR Capacity: 9,2 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.