

KOMATSU FORKLIFT TRUCKS, DIESEL FD FD45-7



ENGINE

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 200 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 200 hours*

DIFFERENTIAL

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 6 months/ 1200 hours*

USE

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 6 months/ 1200 hours*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 200 hours*

USE

Initial service

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 200 hours*

KOMATSU FORKLIFT TRUCKS, DIESEL FD FD45-7



TORQFLOW TRANSMISSION Torqflow

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Change every 3 months/ 600 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Change every 200 hours

HYDRAULIC SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Change every 6 months/ 1200 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| | | |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Change every 200 hours

HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

Change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|---------------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

KOMATSU FORKLIFT TRUCKS, DIESEL FD FD45-7



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.