

KOMATSU FORKLIFT TRUCKS, ELECTRIC FB FB19SH-1 ASX-HP (K06053B ->)

**GEARBOX**

Capacity: 10 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM

Capacity: 42 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32****PRODUCT RECOMMENDATION 2****Perlus AF 32**

Check every 40 hours, change every 12 months/ 2000 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,15 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3**

Check every 2 months/ 350 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES**USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.