

# KOMATSU FORKLIFT TRUCKS, ELECTRIC FB FB20M-2R TX (2008 AND AFTER)



## REDUCTION GEARS

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 1000 hours*

## HYDRAULIC SYSTEM

Capacity: 35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus AF 46***Check every 1000 hours, change every 24 months/ 3000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 1000 hours*

## OIL IMMERSSED BRAKES

Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032***Check every 1000 hours, change every 24 months/ 3000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.