

# KOMATSU FORKLIFT TRUCKS, ELECTRIC FB FB45SH-1 CBX (500001A ->)



## DIFFERENTIAL + TRANSFERBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 3 months/ 600 hours, change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1 months/ 200 hours*

## HYDRAULIC SYSTEM

Capacity: 72 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 3 months/ 600 hours, change every 6 months/ 1200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 1 months/ 200 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,47 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 8 hours, change every 6 months/ 1200 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or*

PRODUCT RECOMMENDATION

# KOMATSU FORKLIFT TRUCKS, ELECTRIC FB FB45SH-1 CBX (500001A ->)



*inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*