PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD20-16

ENGINE
Capacity: 7,5 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Change every 200 hours

DIFFERENTIAL

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 200 hours

TORQFLOW TRANSMISSION Torqflow
Capacity: 9,5 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Change every 200 hours

HYDRAULIC SYSTEM
Capacity: 34 liter (Tank)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 200 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, DIESEL - BX50 SERIES -16/17 FD20-16

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 9,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367