## KOMATSU FORKLIFT TRUCKS, DIESEL - FH SERIES FH-1 FH50-1 KOMATSU SAA4D95LE-5-C T4I (138001 ->)



| ENGINE Komatsu SAA4D95LE-5<br>Capacity: 11 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                         |          |
| Dieselfleet MSP 15W-40                           |          |
|  |          |

Check every 8 hours, change every 3 months/ 500 hours

| DIFFERENTIAL FRONT<br>Capacity: 11 liter                       |  |          |
|--|--|----------|
| USE  |  | CLIMATE  |
| Normal   |  | Moderate |
| PRODUCT RECOMMENDATION 1                                       |  |          |
| Agrifluid HT-Plus  |  |          |
| Check even 1 months 200 hours change even 6 months (1200 hours |  |          |

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

| POWER TAKE OFF<br>Capacity: 5,5 liter                      |  |          |
|--|--|----------|
| USE  |  | CLIMATE  |
| Normal   |  | Moderate |
| PRODUCT RECOMMENDATION 1                                   |  |          |
| Gear Oil Alcat 10W   |  |          |
| Check over 4 months (200 hours, checks, checks) (200 hours |  |          |

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

## HYDRAULIC SYSTEM

Capacity: 110 liter (Hydraulic system including tank), Capacity: 83 liter (Hydraulic tank)

We are unable to give a standard recommendation for this component. Please contact our service department.

| GREASE POINTS/NIPPLES    |                             |                          |
|--------------------------|-----------------------------|--------------------------|
| USE                      |                             | CLIMATE                  |
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q11 Xtreme Duty Grease EP 2 | Q5 MP Calcep Grease EP 2 |

## KOMATSU FORKLIFT TRUCKS, DIESEL - FH SERIES FH-1 FH50-1 KOMATSU SAA4D95LE-5-C T4I (138001 ->)



| COOLING SYSTEM<br>Capacity: 9 liter |                          |          |
|-------------------------------------|--------------------------|----------|
| USE                                 |                          | CLIMATE  |
| Normal                              |                          | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15+                      | Coolant SP 12            |          |
|                                     |                          |          |

Check every 8 hours, change every 24 months/ 4000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.