## KOMATSU FORKLIFT TRUCKS, DIESEL -TUSK EX20 SERIES 2200PD-8 KOMATSU SAA6D107E-1 (7001 ->)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 8 hours, change every 3	3 months/ 500 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Check every 8 hours, change every 3	months/ 500 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 1 months/ 200 hours		·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

TRANSMISSION POWERSHIFT Torqflow

Capacity: 40 liter

## KOMATSU FORKLIFT TRUCKS, DIESEL -TUSK EX20 SERIES 2200PD-8 KOMATSU SAA6D107E-1 (7001 ->)



DIFFERENTIAL FRONT Capacity: 20 liter (Including final drive	e case)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 600 hours, ch	nange every 6 months/ 1200 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Check every 3 months/ 600 hours, ch	nange every 6 months/ 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1 months/ 200 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Change every 1 months/ 200 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 1 months/ 200 hours, change	e every 6 months/ 1200 hours	
USE		CLIMATE
use Initial service		climate Moderate
Initial service		

## KOMATSU FORKLIFT TRUCKS, DIESEL -TUSK EX20 SERIES 2200PD-8 KOMATSU SAA6D107E-1 (7001 ->)



HYDRAULIC SYSTEM Capacity: 170 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 8 hours, change every 6 mon	ths/ 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 1 months/ 200 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 8 hours, change even	v 6 months/ 1200 hours	1

BRAKE COOLING OIL Capacity: 14,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Chook over 1 months/200 hours of	ango ayany 6 mantha/ 1200 hayira	·	

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.