KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG40ZT2US-8 NISSAN TB45E TIER 1 (130001A ->



ENGINE Missan TE46E Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Check every 8 hours, change every 1	months/ 200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Change every 1 months/ 200 hours		

enange every i menane zee neare		
DIFFERENTIAL		
Capacity: 13 liter		
JSE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 3 months/ 600 hours, chang	e every 6 months/ 1200 hours	
JSE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Check every 3 months/ 600 hours, chang	e every 6 months/ 1200 hours	
JSE		CLIMATE
nitial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1 months/ 200 hours		
JSE		CLIMATE
nitial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Change every 1 months/ 200 hours		-
Change every 1 months/ 200 hours USE Initial service PRODUCT RECOMMENDATION 1 SP Gear 5015	PRODUCT RECOMMENDATION 2	

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG40ZT2US-8 NISSAN TB45E TIER 1 (130001A ->



Capacity: 16,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 200 hours, change every 6 m	onths/ 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 1 months/ 200 hours		

HYDRAULIC SYSTEM Capacity: 41,64 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Check every 8 hours, change every	/ 6 months/ 1200 hours	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Change every 1 months/ 200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 8 hours, change every 6 mg	oths/ 1200 hours	

Check every 8 hours, change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

PRODUCT RECOMMENDATION

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG40ZT2US-8 NISSAN TB45E TIER 1 (130001A ->



COULTE STEM Capacity: 14 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chaok ayang a hayra ahanga ayang	12 months / 2400 hours		

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.