## KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG45T2-8 NISSAN TB45E TIER 2 (135001A ->) (2007



ENCINE Nissan T345E Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Check every 8 hours, change every 1 i	months/ 200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30	
Change every 1 months/ 200 hours		·

<b>DIFFERENTIAL</b> Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Gearlube GL-5 80W-90		

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1 months/ 200 hours

USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	SP Gear 1071		
Change every 1 months/ 200 hours	· · · · · · · · · · · · · · · · · · ·	'	

Change every 1 months/ 200 hours

## KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG45T2-8 NISSAN TB45E TIER 2 (135001A ->) (2007



PRANSMISSION FOLVERSHIFT Torqflow Capacity: 16,1 liter	· ·	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 200 hours, change every 6 m	nonths/ 1200 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 1 months/ 200 hours		

HYDRAULIC SYSTEM Capacity: 32,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 32	Perlus AF 32		
Check every 8 hours, change every	6 months/ 1200 hours		

Check every 8 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Change every 1 months/ 200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 8 hours, change every	6 months/ 1200 hours	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

PRODUCT RECOMMENDATION

## KOMATSU FORKLIFT TRUCKS, LPG/PETROL - CX20 SERIES -8 FG45T2-8 NISSAN TB45E TIER 2 (135001A ->) (2007



COCLING SYSTEM Capacity: 14 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chack avery 8 hours, change avery	12 months/2400 hours		

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.