

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK AX/BX20 SERIES -14/- 17 300CG-17 NISSAN K21



ENGINE Nissan K21
Capacity: 4,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Check every 8 hours, change every 3 months/ 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30

Change every 1 months/ 200 hours

DIFFERENTIAL
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1 months/ 200 hours

TRANSMISSION POWERSHIFT Torqflow
Capacity: 11,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 3 months/ 600 hours, change every 6 months/ 1200 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Change every 1 months/ 200 hours

KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK AX/BX20 SERIES -14/- 17 300CG-17 NISSAN K21

**HYDRAULIC SYSTEM**

Capacity: 18,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 8 hours, change every 6 months/ 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

*Change every 1 months/ 200 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

*Check every 8 hours, change every 6 months/ 1200 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 10,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 12 months/ 2400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.