## KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK AX/BX50 SERIES -16/-20 600PGSH-16 NISSAN K25 TIER 2



Synfleet SHPD 10W-40	Dieselfleet MSP 10W-30		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
EACINE Alasara (25 Capacity: 3,8 liter			

Check every 8 hours, change every 3 months/ 500 hours

DIFFERENTIAL Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

TORQFLOW TRANSMISSION Torqflow Capacity: 9,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check avery 1 months/200 hours change avery 6 months/1200 hours		

Check every 1 months/ 200 hours, change every 6 months/ 1200 hours

HYDRAULIC SYSTEM Capacity: 55 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 32	Perlus AF 32		

Check every 8 hours, change every 6 months/ 1200 hours

HYDRAULIC BRAKE SYSTEM Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Charle avery 9 hours abando avery 12 ma	ntha/2400 hours	

Check every 8 hours, change every 12 months/ 2400 hours

## KOMATSU FORKLIFT TRUCKS, LPG/PETROL - TUSK AX/BX50 SERIES -16/-20 600PGSH-16 NISSAN K25 TIER 2



CREASE POINTE/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 9,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Check every 8 hours, change every 12	months/ 2400 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.