

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC05-6 PERKINS 103.09 (5001 -> 11300)



**ENGINE** Perkins 103-09  
Capacity: 3,65 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Change every 250 hours/ 6 months*

### FINAL DRIVES

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

### HYDRAULIC SYSTEM

Capacity: 24,8 liter, Capacity: 18,3 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Change every 2000 hours*

### COOLING SYSTEM

Capacity: 3,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*