

KOMATSU TRACKED EXCAVATORS PC/HB

PC130-6 (1999-2004)



ENGINE Komatsu S4D102E-1
Capacity: 17,5 liter, Capacity: 17 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 8 hours, change every 250 hours

POWER TAKE OFF

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

Check every 2000 hours

HYDRAULIC SYSTEM

Capacity: 100 liter (Hydraulic tank), Capacity: 90 liter (Refill), Capacity: 140 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 3

Perlus H 46

Check every 8 hours, change every 5000 hours

USE	CLIMATE
50% use of breaker	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 3

Perlus H 46

Check every 8 hours, change every 1500 hours

USE	CLIMATE
100% use of breaker	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 3

Perlus H 46

Check every 8 hours, change every 1000 hours

KOMATSU TRACKED EXCAVATORS PC/HB

PC130-6 (1999-2004)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 100 hours

COOLING SYSTEM

Capacity: 18,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 24 months/ 4000 hours

SWING REDUCTION UNIT

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 100 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 250 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.