

KOMATSU TRACKED EXCAVATORS PC/HB

PC138US-8 ECOT3 20001-> (2008-2013)



ENGINE Komatsu SAA4D95LE-5
Capacity: 11,5 liter (Dry fill), Capacity: 11 liter (Service fill)

USE	CLIMATE
Preferred, fuel sulfur level < 0,5%	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Preferred, fuel sulfur level 0,5%-1%	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Alternative, fuel sulfur level <0,5%	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Alternative, fuel sulfur level 0,5-1%	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Preferred, fuel sulfur level >1%, flexible (fluid analysis)	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Check every 10 hours

USE	CLIMATE
Alternative, fuel sulfur level >1%, flexible (fluid analysis)	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Synfleet SHPD 10W-40

Check every 10 hours

KOMATSU TRACKED EXCAVATORS PC/HB

PC138US-8 ECOT3 20001-> (2008-2013)

**POWER TAKE OFF**

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 120 liter (Dry fill), Capacity: 69 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2

Perlus H 46*Check every 10 hours, change every 5000 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Q11 Xtreme Duty Grease EP 2*Check every 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 100 hours***COOLING SYSTEM**

Capacity: 12,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Check every 10 hours, change every 24 months/ 4000 hours*

KOMATSU TRACKED EXCAVATORS PC/HB

PC138US-8 ECOT3 20001-> (2008-2013)

**SWING REDUCTION UNIT**

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 100 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 2,1 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 250 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.