PRODUCT RECOMMENDATION

KOMATSU TRACKED EXCAVATORS PC/HB PC14R-2 KOMATSU 3D67E-1A (F00003 ->) (2005-2008)

ENGINE Komatsu 3D67E-1
Capacity: 3,6 liter (Dry fill), Capacity: 3,3 liter (Service fill)

USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 500 hours

USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Change every 500 hours

USE		CLIMATE
Normal, fuel sulfur level < 0.5 %		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 500 hours

HYDRAULIC SYSTEM
Capacity: 23,8 liter (Dry fill), Capacity: 15,2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Check every 8 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 8 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KOMATSU TRACKED EXCAVATORS PC/HB PC14R-2 KOMATSU 3D67E-1A (F00003 ->) (2005-2008)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 3,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15+	**Coolant SP 12**	

Check every 8 hours, change every 24 months/ 2000 hours

TRAVEL REDUCTION UNIT
Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367