

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC240LC-7K K40001-> (2002-2005)



**ENGINE** Komatsu SAA6D102E-2  
Capacity: 26,3 liter (Dry fill), Capacity: 24 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Change every 250 hours/ 6 months*

### FINAL DRIVES

Capacity: 4,5-4,7 liter

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30**

*Change every 250 hours/ 6 months*

USE	CLIMATE
Subsequently	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30**

*Change every 1000 hours*

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC240LC-7K K40001-> (2002-2005)



### HYDRAULIC SYSTEM

Capacity: 246 liter (Dry fill), Capacity: 166 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 2000 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 250 hours/ 6 months*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

Capacity: 23,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

### DAMPER CASE

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Change every 2000 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Change every 250 hours/ 6 months*

# KOMATSU TRACKED EXCAVATORS PC/HB

## PC240LC-7K K40001-> (2002-2005)



### SWING REDUCTION UNIT

Capacity: 6,6 liter

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 250 hours/ 6 months*

USE	CLIMATE
Subsequently	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.