PRODUCT RECOMMENDATION

KOMATSU TRACKED EXCAVATORS PC/HB
PC300LCSE-8 ECOT3 (2007-2013)

ENGINE Komatsu SAA6D114
Capacity: 38 liter, Capacity: 35 liter (Refill)

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 15W-40		

Check every 8 hours, change every 500 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 8 hours, change every 500 hours

HYDRAULIC SYSTEM
Capacity: 365 liter, Capacity: 188 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	**Perlus H 46**	

Check every 8 hours, change every 5000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q11 Xtreme Duty Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 100 hours

COOLING SYSTEM
Capacity: 32 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

Check every 8 hours, change every 24 months/ 4000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KOMATSU TRACKED EXCAVATORS PC/HB
PC300LCSE-8 ECOT3 (2007-2013)

DAMPER CASE
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 1000 hours

SWING PINION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q11 Xtreme Duty Grease EP 2**	**Q5 MP Calcep Grease EP 2**

Change every 500 hours

SWING REDUCTION UNIT
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 500 hours, change every 1000 hours

TRAVEL REDUCTION UNIT
Capacity: 9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 500 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367