KOMATSU TRACKED EXCAVATORS PC/HB PC450-6 (1997-1999)



ENGINE Capacity: 42 liter (Refill), Capacity: 44,7 liter (Specified)		
	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Asyntho 5W-30	
	PRODUCT RECOMMENDATION 2	

Change every 250 hours/ 6 months

FINAL DRIVES Capacity: 11,5 liter (Refill), Capacity: 12 liter (Specified)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			

HYDRAULIC SYSTEM Capacity: 270 liter (Refill), Capacity:	370 liter (Specified)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 2000 hours		

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

COOLING SYSTEM Capacity: 42,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

KOMATSU TRACKED EXCAVATORS PC/HB PC450-6 (1997-1999)



DAMPER CASE Capacity: 1,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Change every 2000 hours	

SWING REDUCTION UNIT Capacity: 21,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.