KOMATSU TRACKED EXCAVATORS PC/HB PC750SE-6K



ENGINE Cummins QSK19				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
	<u> </u>			

Change every 250 hours/ 6 months

FINAL DRIVES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

POWER TAKE OFF			
USE	CLIMATE		
Normal	Mediterranean		
PRODUCT RECOMMENDATION 1			
Multifleet SCD 30			

HYDRAULIC SYSTEM				
use Normal		climate Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40		
Change every 2000 hours	1			

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

PRODUCT RECOMMENDATION

KOMATSU TRACKED EXCAVATORS PC/HB PC750SE-6K



SWING REDUCTION UNIT				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.