KOMATSU BACKHOE LOADERS WB WB97R-5 KOMATSU SAA4D104E-1 (2005



AND AFTER)

ENGINE Komatsu SAA4D104E-1 Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Armado Synth 5W-30
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Armado Synth 5W-30

Change every 500 hours

DIFFERENTIAL FRONT Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours	·	

DIFFERENTIAL REAR Capacity: 15 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Change every 1000 hours	'		

FINAL REDUCTION GEARS Capacity: 7,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Change every 1000 hours		•	

TRANSMISSION Capacity: 20 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 2000 hours		

Dollegoorweg 15

7602 EC Almelo

KOMATSU BACKHOE LOADERS WB WB97R-5 KOMATSU SAA4D104E-1 (2005



AND AFTER)

HYDRAULIC SYSTEM Capacity: 98 liter (Dry fill), Capacity:	40 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 2000 hours		

HYDRAULIC BRAKE SYSTEM Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 2000 hours	·

COOLING SYSTEM Capacity: 15 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.