

KOMATSU TELEHANDLERS LW/WH WH613

(2004-2009)



ENGINE Komatsu 4D104E-1
Capacity: 12,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Armado Synth 5W-30

Check every 8 hours, change every 6 months/ 500 hours

DIFFERENTIAL FRONT
Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

DIFFERENTIAL REAR
Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

HUB REDUCTIONS FRONT
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

HUB REDUCTIONS REAR
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

KOMATSU TELEHANDLERS LW/WH WH613

(2004-2009)



TRANSMISSION

Capacity: 13,5 liter (Dry fill), Capacity: 11,7 liter (Refill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 3 months/ 250 hours, change every 12 months/ 1000 hours*

HYDRAULIC SYSTEM

Capacity: 107 liter (Hydraulic tank), Capacity: 95 liter (Refill), Capacity: 117 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 6 months/ 500 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
Initial service (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Change every 500 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 8 hours, change every 24 months/ 2000 hours*

KOMATSU TELEHANDLERS LW/WH WH613

(2004-2009)

**COOLING SYSTEM**

Capacity: 20 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26**

Check every 8 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.