PRODUCT RECOMMENDATION

KRAMER WHEELED LOADERS 418 PERKINS 704.30 (2001-2003)

ENGINE Perkins 704-30

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SHPD 20W-50**

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT AND REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1200 hours

GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 600 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KRAMER WHEELED LOADERS 418 PERKINS 704.30 (2001-2003)

PLANETARY GEARS FRONT AND REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 1200 hours

HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	**Perlus H 68**	**Perlus AF 46**

Change every 1200 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 1200 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367