## **KRAMER SHOVEL LOADERS 212E**



| USE                      | CLIMATE       |
|--------------------------|---------------|
| Normal                   | Tropical      |
| PRODUCT RECOMMENDATION 1 |               |
| Multifleet SCD 40        |               |
| Change every 150 hours   | ·             |
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| Multifleet SCD 30        |               |
| Change every 150 hours   |               |
| USE                      | CLIMATE       |
| Normal                   | Cold          |
| PRODUCT RECOMMENDATION 1 |               |
| Multifleet SCD 20W-20    |               |
| Change every 150 hours   |               |
| USE                      | CLIMATE       |
| Normal                   | Arctic        |
| PRODUCT RECOMMENDATION 1 |               |
| Multifleet SCD 10W       |               |
| Change every 150 hours   |               |

| DIFFERENTIAL FRONT       |                             |          |  |
|--------------------------|-----------------------------|----------|--|
| USE                      |                             | CLIMATE  |  |
| Normal                   |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-4 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |  |
| Change every 1200 hours  |                             |          |  |

| FINAL DRIVES FRONT AND REAR |                             |          |  |
|-----------------------------|-----------------------------|----------|--|
| USE                         |                             | CLIMATE  |  |
| Normal                      |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-4 80W-90        | Unigear HS GL-3/GL-5 80W-90 |          |  |
| Change every 1200 hours     |                             | •        |  |

## **KRAMER SHOVEL LOADERS 212E**



| GEARBOX/REAR AXLE DIFFERENTIAL |          |  |  |
|--------------------------------|----------|--|--|
| USE                            | CLIMATE  |  |  |
| Normal                         | Moderate |  |  |
| PRODUCT RECOMMENDATION 1       |          |  |  |
| ATF Dexron II-D                |          |  |  |
| Change every 600 hours         | ·        |  |  |

| HYDRAULIC SYSTEM POWER STEERING |                          |          |  |
|---------------------------------|--------------------------|----------|--|
| USE                             |                          | CLIMATE  |  |
| Normal                          |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2 |          |  |
| ATF Dexron II-D                 | ATF-A                    |          |  |
| Change every 1200 hours         |                          |          |  |

| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.