KUBOTA TRACKED EXCAVATORS K/KH/KX/U K008A KUBOTA D722 (2001-2003)



| Capacity: 2,8 liter | | 0.111.75 |
|--------------------------|--------------------------|--------------------------|
| use Normal | | сымате Mediterranean |
| PRODUCT RECOMMENDATION 1 | | Mediterranean |
| Multifleet SCD 30 | | |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |
| Change every 50 hours | | |
| USE | | COL |
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |

KUBOTA TRACKED EXCAVATORS K/KH/KX/U K008A KUBOTA D722 (2001-2003)



| HYDRAULIC SYSTEM | |
|--------------------------|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 68 | |
| Change every 1000 hours | |
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 1000 hours | |
| USE | CLIMATE |
| Normal | Cold |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 32 | |
| Change every 1000 hours | |

| PINS + BUSHINGS | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| SWING REDUCTION UNIT | | | |
|--------------------------|-----------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | |
| Change every 1000 hours | ' | , | |

| TRACK ROLLERS + FRONT IDLERS | | | | |
|------------------------------|-----------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | | |

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U K008A KUBOTA D722 (2001-2003)



| TRAVEL REDUCTION UNIT | | |
|--------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 1000 hours | · | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.