

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4

(T4F) (2013 AND AFTER)



ENGINE Kubota V3307-CR-TE4
Capacity: 9,7 liter

USE	CLIMATE
Normal, fuel sulfur level < 15 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 159 liter (2-piece boom specification), Capacity: 75 liter (Hydraulic tank), Capacity: 146 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Breaker use < 40%	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 800 hours

USE	CLIMATE
Breaker use 40 - 60%	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 400 hours

USE	CLIMATE
Breaker use 60 - 80%	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 300 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4 (T4F) (2013 AND AFTER)



USE		CLIMATE
Breaker use > 80%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
<i>Check every 10 hours, change every 200 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM		
Capacity: 10,5 liter, Capacity: 1,3 liter (Reserve tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 10 hours, change every 24 months</i>		

CARRIER ROLLERS		
Capacity: 0,8 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
<i>Change every 2000 hours</i>		

IDLER FRONT		
Capacity: 0,08 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
<i>Change every 2000 hours</i>		



KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX080-4 KUBOTA V3307-CR-TE4 (T4F) (2013 AND AFTER)

**TRACK ROLLER**

Capacity: 0,8 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 2000 hours***TRAVEL REDUCTION UNIT**

Capacity: 1,3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.