

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX121-3S KUBOTA V2203-M-E2BH



ENGINE Kubota V2203-M-E2B
Capacity: 8,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 50*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 50*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40*Change every 50 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20*Change every 50 hours*

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX121-3S KUBOTA V2203-M-E2BH



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
<i>Change every 50 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 46 liter (Hydraulic tank), Capacity: 75 liter (System)		
USE		CLIMATE
Breaker use 40 - 60%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Check every 10 hours, change every 400 hours</i>		

USE		CLIMATE
Breaker use 40 - 60%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
<i>Check every 10 hours, change every 400 hours</i>		

USE		CLIMATE
Breaker use 60 - 80%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Check every 10 hours, change every 300 hours</i>		

USE		CLIMATE
Breaker use 60 - 80%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
<i>Check every 10 hours, change every 300 hours</i>		

USE		CLIMATE
Breaker use > 80%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
<i>Check every 10 hours, change every 200 hours</i>		

USE		CLIMATE
Breaker use > 80%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
<i>Check every 10 hours, change every 200 hours</i>		

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX121-3S KUBOTA V2203-M-E2BH



USE		CLIMATE
Breaker use < 20%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 1000 hours

USE		CLIMATE
Breaker use < 20%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 1000 hours

USE		CLIMATE
Breaker use 20 - 40%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 10 hours, change every 800 hours

USE		CLIMATE
Breaker use 20 - 40%		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	

Check every 10 hours, change every 800 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 7,4 liter (Radiator), Capacity: 1,6 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX121-3S KUBOTA V2203-M-E2BH

**TRAVEL REDUCTION UNIT**

Capacity: 0,5 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.