

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX71-3S KUBOTA V1505-E4-B



**ENGINE** Kubota V1505-E4B  
Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 50 hours*

### HYDRAULIC SYSTEM

Capacity: 53 liter (Hydraulic system including tank), Capacity: 38 liter (Hydraulic tank)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 10 hours, change every 1000 hours*

USE	CLIMATE
Breaker use 40 - 60%	Tropical

PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 10 hours, change every 300 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX71-3S KUBOTA V1505-E4-B



USE		CLIMATE
Breaker use 40 - 60%		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Check every 10 hours, change every 300 hours</i>		
USE		CLIMATE
Breaker use 40 - 60%		Cold
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Check every 10 hours, change every 300 hours</i>		
USE		CLIMATE
Breaker use < 20%		Tropical
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		
<i>Check every 10 hours, change every 800 hours</i>		
USE		CLIMATE
Breaker use < 20%		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Check every 10 hours, change every 800 hours</i>		
USE		CLIMATE
Breaker use < 20%		Cold
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Check every 10 hours, change every 800 hours</i>		
USE		CLIMATE
Breaker use > 60%		Tropical
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		
<i>Check every 10 hours, change every 200 hours</i>		
USE		CLIMATE
Breaker use > 60%		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Check every 10 hours, change every 200 hours</i>		

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX71-3S KUBOTA V1505-E4-B



USE		CLIMATE
Breaker use > 60%		Cold
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Check every 10 hours, change every 200 hours</i>		
USE		CLIMATE
Breaker use 20 - 40%		Tropical
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		
<i>Check every 10 hours, change every 400 hours</i>		
USE		CLIMATE
Breaker use 20 - 40%		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		
<i>Check every 10 hours, change every 400 hours</i>		
USE		CLIMATE
Breaker use 20 - 40%		Cold
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		
<i>Check every 10 hours, change every 400 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

COOLING SYSTEM		
Capacity: 4,3 liter (Radiator), Capacity: 1,1 liter (Reserve tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>
<i>Change every 24 months</i>		

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX71-3S KUBOTA V1505-E4-B

**TRAVEL REDUCTION UNIT**

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 100 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*