

LIEBHERR TRACKED ROPE OPERATED CRANES HS HS873HD D9804TI-E (1998 AND AFTER)



ENGINE Liebherr D9408TI-E
Capacity: 31 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 8 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Check every 8 hours, change every 500 hours

TRANSFERBOX
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 8 hours, change every 500 hours

HYDRAULIC SYSTEM
Capacity: 1200 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 8 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

GREASE POINTS/NIPPLES SWING GEAR

We are unable to give a standard recommendation for this component. Please contact our service department.

LIEBHERR TRACKED ROPE OPERATED CRANES HS HS873HD D9804TI-E (1998 AND AFTER)



COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 11	Coolant -38 Organic NF	Coolant -26

SWING REDUCTION UNIT

Capacity: 14,5 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 25 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

WINCH REDUCTION UNIT

Capacity: 12 liter (16t (each)), Capacity: 18 liter (20t (each)), Capacity: 26 liter (25t (each)), Capacity: 36 liter (30t (each))

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

WINCH REDUCTION UNIT MAIN BOOM CONTROL

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.