PRODUCT RECOMMENDATION

LIFTLUX SELF PROPELLED PLATFORMS, ELECTRIC SL 153-12E 2WD

HYDRAULIC SYSTEM
Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 8 hours, change every 1200 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

ELECTRIC MOTOR BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367