

# LINDE FORKLIFT TRUCKS, DIESEL (1402 SERIES) H180 1402-01 / CUMMINS QSB6.7 (2009 AND AFTER)



**ENGINE** Cummins QSB6.7  
Capacity: 35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Armado Synth 5W-30</b>

*Change every 50 hours*

**DIFFERENTIAL**  
Capacity: 75 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 85W-140</b>		

*Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 1071</b>	<b>Syngear TDL 75W-90</b>

*Check every 500 hours, change every 2000 hours*

# LINDE FORKLIFT TRUCKS, DIESEL (1402 SERIES) H180 1402-01 / CUMMINS QSB6.7 (2009 AND AFTER)

**HUB REDUCTIONS**

Capacity: 7 liter (each hub)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140***Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**SP Gear 1071**

PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 500 hours, change every 2000 hours***STEER AXLE HUBS**

Capacity: 4 liter (each hub)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140***Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**SP Gear 1071**

PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 500 hours, change every 2000 hours*

# LINDE FORKLIFT TRUCKS, DIESEL (1402 SERIES) H180 1402-01 / CUMMINS QSB6.7 (2009 AND AFTER)

**TRANSMISSION 3/3**

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

*Check every 10 hours, change every 1000 hours*

**HYDRAULIC SYSTEM**

Capacity: 430 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Heavy Duty		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus AF 100</b>		

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Normal & Heavy duty		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Alternative, normal & heavy duty		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Alternative, heavy duty		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Check every 10 hours, change every 3000 hours*

**HYDRAULIC SYSTEM WET BRAKES**

Capacity: 106 liter (Hydraulic tank), Capacity: 6 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

# LINDE FORKLIFT TRUCKS, DIESEL (1402 SERIES) H180 1402-01 / CUMMINS QSB6.7 (2009 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

## COOLING SYSTEM

Capacity: 45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*