

# LJUNGBY MASKIN WHEELED LOADERS

## L11 MERCEDES OM906LA TIER 3 / STAGE

### IIIA (2010-2012)



**ENGINE** Mercedes-Benz OM906LA  
Capacity: 29 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	

*Check every 10 hours, change every 500 hours*

**DIFFERENTIAL FRONT** ZF MT-L3075  
Capacity: 30 liter (+ hub reductions)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 1000 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 500 hours*

**DIFFERENTIAL REAR** ZF MT-L3075  
Capacity: 30 liter (+ hub reductions)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 1000 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 500 hours*

# LJUNGBY MASKIN WHEELED LOADERS

## L11 MERCEDES OM906LA TIER 3 / STAGE

### IIIA (2010-2012)



#### HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 1000 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 500 hours*

#### HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 1000 hours*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	<b>Gearlube LS 80W-90</b>

*Change every 500 hours*

#### TRANSMISSION ZF Ergopower WG 160 4/3

Capacity: 21 liter (Change capacity), Capacity: 36 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

*Change every 1000 hours*

# LJUNGBY MASKIN WHEELED LOADERS

## L11 MERCEDES OM906LA TIER 3 / STAGE

### IIIA (2010-2012)

**HYDRAULIC SYSTEM**

Capacity: 115 liter (Change capacity), Capacity: 175 liter (System)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

*Check every 10 hours, change every 2000 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Check every 10 hours, change every 1000 hours***CENTRAL LUBRICATION SYSTEM GREASE** Lincoln

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		

**GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 4000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.