MAEDA MINI CRAWLER CRANES MC-285-2 CRM



JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Change every 500 hours		·
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40
Change every 500 hours		
use Normal		climate Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Change every 500 hours	·	·
use Initial service		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Change every 250 hours		·
use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Dieselfleet CD+ 15W-40
Change every 250 hours		
use Initial service		climate Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
Change every 250 hours		

MAEDA MINI CRAWLER CRANES MC-285-2 CRM



WINCH REDUCER Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP 320	
Change every 1000 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Abacot MEP 320	
Change every 250 hours	

HYDRAULIC SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 32	Perlus H 22
Change every 1000 hours	'	

COOLING SYSTEM Capacity: 2,1 liter			
use Normal		сымате Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 1000 hours	1	1	

MAEDA MINI CRAWLER CRANES MC-285-2 CRM



SWING REDUCTION UNIT Capacity: 0,6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Abacot MEP 320		
Change every 1000 hours		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Abacot MEP 320		
Change every 250 hours		
TRAVEL REDUCTION UNIT Capacity: 0,33 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Abacot MEP 320		
Change every 1000 hours		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Abacot MEP 320

Change every 250 hours