

MANITOU WHEELED LOADERS AL AL80

**ENGINE**

Capacity: 10 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40****DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 4,2 liter (20 km/h version), Capacity: 3,8 liter (30 km/h version)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 50 hours, change every 1500 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 500 hours***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 5,1 liter (20 km/h version), Capacity: 5,5 liter (30 km/h version)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Check every 50 hours, change every 1500 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 500 hours*

MANITOU WHEELED LOADERS AL AL80

**HUB REDUCTIONS FRONT**

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours***HUB REDUCTIONS REAR**

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 100 liter (Change capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Check every 10 hours, change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 1500 hours*

MANITOU WHEELED LOADERS AL AL80



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.