

MANITOU MANISCOPIC MT/MTA MT 6034T

JOHN DEERE 4045T TIER 3 (16150 - 16158)



ENGINE John Deere 4045 T
Capacity: 14,7 liter

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40

Change every 100 hours

USE	CLIMATE
Normal, fuel sulfur level < 0,1 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 250 hours/ 3 months

DIFFERENTIAL FRONT Dana
Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 250 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Dana
Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 0,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 250 hours, change every 1000 hours/ 12 months

MANITOU MANISCOPIC MT/MTA MT 6034T

JOHN DEERE 4045T TIER 3 (16150 - 16158)

**HUB REDUCTIONS REAR**

Capacity: 0,5 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 250 hours, change every 1000 hours/ 12 months

TRANSMISSION POWERSHIFT Clark T12000 3/3

Capacity: 22,7 liter (+ cooler)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 10 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 133 liter (Hydraulic system including tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 2000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 10 hours, change every 1000 hours/ 12 months

MANITOU MANISCOPIC MT/MTA MT 6034T JOHN DEERE 4045T TIER 3 (16150 - 16158)

**GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2****COOLING SYSTEM**

Capacity: 16,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.