

MANITOU MANISCOPIC MLT MLT 625-75 H S1-E3 KUBOTA V3307-T-E3B (2011 AND AFTER)



ENGINE Kubota V3307 Di-T3
Capacity: 11,2 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Dieselfleet MSP 15W-40
--	---	--

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT Dana
Capacity: 4 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 2 Agrifluid HT	
---	--	--

Check every 250 hours, change every 6 months/ 500 hours

DIFFERENTIAL REAR Dana
Capacity: 3,8 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 2 Agrifluid HT	
---	--	--

Check every 250 hours, change every 6 months/ 500 hours

HUB REDUCTIONS FRONT
Capacity: 0,9 liter (each)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 250 hours, change every 1000 hours/ 12 months

USE Initial service	CLIMATE Moderate
-------------------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 250 hours, change every 6 months/ 500 hours

MANITOU MANISCOPIC MLT MLT 625-75 H S1-E3 KUBOTA V3307-T-E3B (2011 AND AFTER)



HUB REDUCTIONS REAR

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 6 months/ 500 hours

TRANSMISSION HYDROSTATIC

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 6 months/ 500 hours

HYDRAULIC SYSTEM

Capacity: 115 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Perlus H 46

Check every 10 hours, change every 1000 hours/ 12 months

COOLING SYSTEM

Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.