

# MANITOU MANITRANSIT RANGE

## TMD/TME/TMP/TMT/TMV TMP 55 PERKINS

### 404C--22 TIER 2 (751864 ->)



**ENGINE** Perkins 404C-22  
Capacity: 5,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 200 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel MSP 15W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 40 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

*Check every 50 hours, change every 800 hours/ 12 months*

#### GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

# MANITOU MANITRANSIT RANGE

## TMD/TME/TMP/TMT/TMV TMP 55 PERKINS

### 404C--22 TIER 2 (751864 ->)



#### GREASE POINTS/NIPPLES MAST CARRIER THRUST PADS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Change every 10 hours*

#### COOLING SYSTEM

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 10 hours, change every 800 hours/ 12 months*

#### MAST CHAINS

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*