

## MANITOU MASTED RANGE CD/CG CD 35 P

**ENGINE**

Capacity: 7,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40****AXLE OSCILLATION REAR**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2****DIFFERENTIAL**

Capacity: 6 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90****TRANSMISSION**

Capacity: 9 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**ATF Almirol****HYDRAULIC SYSTEM**

Capacity: 75 liter (Hydraulic tank)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 46**

**MANITOU MASTED RANGE CD/CG CD 35 P****HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*