

MECALAC WHEELED EXCAVATORS 11 CXI

(1984-1997)



ENGINE Deutz F4L-913
Capacity: 11 liter

| USE | | CLIMATE |
|-------------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

DIFFERENTIAL FRONT
Capacity: 10,4 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

DIFFERENTIAL REAR
Capacity: 10,4 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

HUB REDUCTIONS
Capacity: 0,7 liter (each hub)

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

HYDRAULIC SYSTEM
Capacity: 130 liter, Capacity: 80 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |

MECALAC WHEELED EXCAVATORS 11 CXI

(1984-1997)



HYDRAULIC BRAKE SYSTEM

Capacity: 2,3 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| LHM + | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

STEERING REDUCTION UNIT

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |

SWING REDUCTION UNIT Brevini

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |

SWING REDUCTION UNIT Hamworthy

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.