MERLO TELESCOPIC HANDLERS, PANORAMIC P30.12 EVS PERKINS 1004.4



(1995-1998)

| ENGINE Perkins 1004.4 | | |
|----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |
| Change every 400 hours/ 6 months | · | · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |
| Change every 400 hours/ 6 months | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |
| Change every 100 hours | • | |

| DIFFERENTIAL Capacity: 5,3 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 400 hours/ 6 months | | |

| GEARBOX Capacity: 4 liter | | |
|----------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 400 hours/ 6 months | | · |

Dollegoorweg 15

7602 EC Almelo

MERLO TELESCOPIC HANDLERS, PANORAMIC P30.12 EVS PERKINS 1004.4



(1995-1998)

| HUB REDUCTIONS Capacity: 1,3 liter | | |
|------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 400 hours/ 6 months | | |

| TRANSMISSION HYDROSTATIC Rexroth Capacity: 12 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 1600 hours/ 12 months | · |

| HYDRAULIC SYSTEM Capacity: 95 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| Change every 1600 hours/ 12 months | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

| COOLING SYSTEM Capacity: 12 liter | | |
|-----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.