

MERLO TELESCOPIC HANDLERS, ROTATING ROTO 40.30 MCSS IVECO NEF N67 NMT (TIER 3) (2011-2015)



ENGINE Iveco NEF N67 MNT
Capacity: 17,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

DIFFERENTIAL REAR
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

HUB REDUCTIONS FRONT
Capacity: 1,5 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

HUB REDUCTIONS REAR
Capacity: 1,5 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

MERLO TELESCOPIC HANDLERS, ROTATING ROTO 40.30 MCSS IVECO NEF N67 NMT (TIER 3) (2011-2015)

**TRANSFERBOX**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

TRANSMISSION HYDROSTATIC

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 1500 hours

HYDRAULIC SYSTEM

Capacity: 190 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 1500 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 50 hours, change every 1500 hours

COOLING SYSTEM

USE		CLIMATE
Flexible, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours

MERLO TELESCOPIC HANDLERS, ROTATING ROTO 40.30 MCSS IVECO NEF N67 NMT (TIER 3) (2011-2015)

**SWING REDUCTION UNIT**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.